



MMA welding transformer

TW 200



The welding transformer TW 200 is robust and reliable. It has good welding units with enough power for the professionals. Cooper windings and fan cooling, good striking and welding properties, applicable for many electrodes. Optionally for 400V or 230V connection.

Technical Data

		TW 200 (Article No. 11112)	
Rated input voltage:		230 V / 50 Hz	400 V / 50 Hz
Mains supply:		with adaptor	without adaptor
Maximum connector cable:		4,4 kVA	7,6 kVA
Maximum input current:		20 A	20 A
Fuse protection (inert):		16 A T	16 A T
Open-circuit voltage:		46 V - 55 V	46 - 55 V
Range of adjustment:		50 A / 20 V till 120 A / 23 V	50 A / 20 V till 180 A / 25 V
Duty cycle	DB:	90 A	90 A
	HSB:	120 A / 60%	180 A / 35%
Current adjustment (stepped):		8	12
Level of protection:			IP21
Insulation class:			H(180°C)
Cooling:		ventilator cooling	
Weight:		27 kg	
Dimension:		450 mm x 220 mm x 330 mm	
Overload protection:		display	
Technical standard:		EN 60 974-1	
Scope of delivery:		complete welding transformer with adaptor	
Option:		E-welding wire set 4m	